

**8.0 Mega Pixel**

**HD VIDEO RECORDING**




ProStalk® 8MP  
PC8000 - ProStalk® 8MP

**FREE** Memory Card

**5.0 Mega Pixel**

**ULTRA LOW GLOW IR LEDs**




ProStalk® 5MP  
PC5500 - ProStalk® 5MP

**FREE** Memory Card

**5.0 Mega Pixel**

**COMPACT**



ProStalk® 5MP  
PC5000 - ProStalk® 5MP

**FREE** Memory Card

**3.0 Mega Pixel**



ProStalk® 3MP  
PC3000 - ProStalk® 3MP

**FREE** Memory Card

**2.0 Mega Pixel**

**ULTRA SMALL**



ProStalk® 2MP  
PC2000 - ProStalk® 2MP

**FREE** Memory Card

## RECORD STILL IMAGES AND AVI VIDEO



- 45° DUAL PIR SENSORS
- SUPER NV IR
- VIDEO MODE
- DATE IMPRINT
- Hi-Res LENS
- BURST MODE
- PAD LOCKABLE
- MOON PHASE
- WEATHER PROOF



ProStalk Nature Cameras are designed primarily to capture images of wildlife and game animals in remote locations. They can also be used for remote surveillance.

The cameras are activated by a wide angle sensor detecting movement. This triggers the fast camera shutter, capturing the wildlife that is in the area. All ProStalk cameras are able to record still images as well as AVI video format.

ProStalk cameras are easy to use and have features that are only present on cameras costing much more.

Choose from the 8MP PC8000, two 5MP models, 3MP or the 2MP model - the smallest nature cameras in the World!

All cameras are supplied with 2GB SD Card, Tree Strap and Instruction book. Batteries are not included.

from **HAWKE**

Model	ProStalk® 8MP - PC8000	ProStalk® 5MP - PC5500	ProStalk® 5MP - PC5000	ProStalk® 3MP - PC3000	ProStalk® 2MP - PC2000
Real Resolution	8.0 MP	5.0 MP	5.0 MP	3.1 MP	2.0 MP
Size	Compact 94x147x46mm	Compact 94x147x46mm	Compact 94x147x46mm	Normal 160x220x60mm	Ultra Small 82x122x41mm
Display	2.5" TFT LCD	2x8 Dot Matrix LCD Display	TN digital screen without backlight	Dot Matrix digital Screen with backlight	TN digital screen without backlight
Motion Sensor	1 PIR, 47 degree, 45 feet range	1 PIR, 42 degree, 66 feet range	1 PIR, 47 degree, 45 feet range	2xPIRs, 48 degree, 45 feet range	1 PIR, 45 degree, 45 feet range
PIR Sensitivity Controller	Yes	Yes	Yes	No	No
IR LED	30 LEDs	52 Ultra Low Glow IR LEDs (15 metres)	30 LEDs (15 metres)	36 LEDs (14 metres)	15 LEDs (10 metres)
Photo Take Delay	5s-60 min (Default: 1 minute)	5s-60 min (Default: 1 minute)	0s-60 min (Default: 1 minute)	1min/5mins/15mins/Customize in Menu (1-60mins)	0s-60 min (Default: 1 minute)
Storage Image Size	SD Card (up to 32G)	SD Card (up to 32G)	SD Card (up to 32G) 2560x1920 (5.0M), 2048x1536 (3.1M), 1280x1024 (1.3M)	SD Card (up to 2G) 2048x1536 (3.1M), 1280x1024 (1.3M), 640x480 (0.35)	SD Card (up to 32G) 1600x1200 (2.0M), 1028x768 (0.8M)
Movie	AVI 640x480, 1280x720 HD Video 15-60 seconds	AVI 640x480 15 seconds fixed length	AVI 640x480 15 seconds fixed length	AVI 320x240 10-90 seconds with sound	AVI 640x480 15 seconds fixed length
Power	8x AA Cell	8x AA Cell	8x AA Cell	4x D Cell	4x AA Cell
Working Time	230 days (subject to 15 day time pictures and 15 night time pictures a day)	180 days (subject to 15 day time pictures and 15 night time pictures a day)	12 Months (12,000 pictures)	3-5 Months (4,000 pictures)	6 Months (6,000 pictures)
External Power	No	No	No	Solar Panel or External Battery	No
Shutter Speed	0.9 Second	0.9 Second	0.9 Second	1.0 Second	0.9 Second

### ProStalk® Accessories

PC3010 - Solar Panel compatible with the PC3000  
ProStalk 3MP model includes batteries

BA7821 - AA Batteries 4 pk

BA7823 - D Cell Batteries 2 pk

External Battery 6V - **CALL FOR PRICING**

Solar Panel

